

2654-62

Pinhole Spy Camera



Key Vaule Highlight

1. Complete hidden security system

Highly integrated with WiFi, Built-in DVR inside this Pinhole spy camera, what you need is simple power, you will have your HD spy camera system running on the sense.

2. Covert Camera

With pinhole design, you can hide this camera in bag, clock, power socket without being detected.

3. Free app for mobile accessing

You can easily watch the live video, check the recording footage on Pinhole spy camera with your mobile phone, tablet or PC computer.

4. Power bank battery support spy camera

With wide range power accepted and ultra low power consumption, this Pinhole spy camera can work with an external battery or power bank. 10000AMH power bank can support up to 48 hours continuous WiFi network streaming and recording.

Mobility

Compact size and battery support allow you to move this camera to different place even put it on the car when you are on the traveling.

6. Easy to setup

This pinhole spy camera has built-in mini AP, you can either connect the camera to internet or to your mobile app directly.

Typical Application

Home

Retail

Convenience Store

Workshop

Office

and others

5.

Specification

Power	
Input voltage	+12 VDC to DC5V
Power consumption	4.5 W (max)
Video	
Sensor type	1/3 Type CMOS Sensor
Sensor pixels	1280x960
Sensitivity	1.0 lx (IR off)
Main-stream Resolution	1280x720@22fps
Sub-stream Resolution	4CIF@25fps
Video compression	H.264 MP (Main Profile)
DWDR	ON/OFF
3D DNR	Yes
Night vision	
IR cuter filter	N/A
Lens	
Lens type	3.7 mm pinhole lens
Field of View	H: 77°
Lens mount	Board mounted
Day & Night	N/A
Audio (optional)	
Audio input	RCA jack connector
Audio output	RCA jack connector
Audio communication	Two-way, full duplex
Audio compression	G.711 (live and recording)
Local Storage	
Memory card slot	Supports up to 128 GB micro SD card (An SD card of Class 8 or higher is recommended for HD recording)
Recording	Continuous recording, Motion/schedule recording
Onvif Protocol	
Profile-S	N/A

Software Control	
Unit configuration	Via web browser or PC surveillance software
Network	
Protocols	HTTP, TCP/IP, ARP, RTSP, RTP, UDP, SMTP, FTP, DHCP, DNS, DDNS, PPPOE, UPNP, NTP, 802.1x
Ethernet	N/A
Wireless	IEEE 802.11b/g/n
PoE	N/A
Mechanical	
Dimensions	42*42*25mm
Weight	TBA
Environmental	
Operating temperature Camera	-20 °C to +55 °C (-4 °F to +131 °F)
Storage temperature	-20 °C to +70 °C (-4 °F to +158 °F)
Humidity	10% to 80% relative humidity (non condensing)
Ordering Information	
Pinhole Spy Camera	2654-62