

2654-48

IP Spy Camera



Key Vaule Highlight

1. 1080p Full HD

This IP spy camera employs SONY EXMOR low lux sensor to deliver high resolution image.

2.Tiny Pinhole Lens

This camera can be deployed to different places without being detected.

3. Free app for mobile accessing

You can easily watch the live video from this IP spy camera on your mobile phone, tablet or PC

4. Complete Open

With onvif profile-S, you can integrate this camera to any other 3rd party Onvif NVRs or VMS software.

5. Easy to setup

This camera supports Power over Ethernet (PoE). Single cat5 cable can carry both power and network to this IP spy camera .

Typical Application

Retail

Convenience Store

Workshop

Logistics center

and others

Specification

Power	
Input voltage	+12 VDC or Power-over-Ethernet
Power consumption	4.5 W (max)
Video	
Sensor type	1/2.8 Type SONY Exmor CMOS Sensor
Sensor pixels	1920x1080
Sensitivity	0.1 lx (IR off)
Main-stream Resolution	1920x1080@25fps; 1280x720@25fps
Sub-stream Resolution	4CIF@25fps; CIF@25fps
Video compression	H.264 MP (Main Profile)
DWDR	ON/OFF
3D DNR	Yes
Lens	
Lens type	3.7 mm pinhole lens
Field of View	H: 77°
Lens mount	Board mounted
Day & Night	Auto
Audio (NOT Included)	
Audio input	RCA jack connector
Audio output	RCA jack connector
Audio communication	Two-way, full duplex
Audio compression	G.711 (live and recording)
Onvif Protocol	
Profile-S	Yes

Software Control	
Unit configuration	Via web browser or PC surveillance software
Network	
Protocols	HTTP, TCP/IP, ARP, RTSP, RTP, UDP, SMTP, FTP, DHCP, DNS, DDNS, PPPOE, UPNP, NTP, 802.1x
Ethernet	10/100 Base-T, auto-sensing, half/full duplex, RJ45
Wireless	N/A
PoE	IEEE 802.3af compliant
Mechanical	
Dimensions	42*42*25mm
Weight	TBA
Environmental	
Operating temperature Camera	-20 °C to +55 °C (-4 °F to +131 °F)
Storage temperature	-20 °C to +70 °C (-4 °F to +158 °F)
Humidity	10% to 80% relative humidity (non condensing)
Ordering Information	
IP Spy Camera	2654-48

Guangzhou

No.3 East Alley, Guangfeng East Road,
Zengchen District, Guangzhou,, 511300,
P.R.China
Tel: +86-20-8244-2660
Fax: +86-20-8274-5925
Email: sales@golbong.com

Shenzhen

1/F Block 295, Jiuwei, Xixiang Town,
Baoan District, Shenzhen, 518000,
P.R.China
Tel: +86-755-81465995
Fax: +86-755-81469770
Email: sales@golbong.com