

2651-57

Smoke Detector Spy Camera



Key Vaule Highlight

1. Intelligent Missing Object Detection

Our smoke detector spy camera can detect the missing the object on the sense and send push message to your mobile phone.

2. Covert Camera

Install the smoke detector spy camera on ceiling give you great advance to monitor the sense without being detected.

3. All-in-One

This camera is a completed hidden security system in a single device. Insert Marco SD card, the smoke detector spy camera will start motion activated recording.

4. Free app for mobile accessing

You can easily watch the live video, check the recording footage from smoke detector spy camera on your mobile phone, tablet or PC.

5. Night vision Compatible.

One of the downside for pinhole camera is the night vision because the pinhole lens is too small to pass enough light, but not with ours. With built-in IR cut filter, this camera can switch to black/white at night to see the infrared, you can use our add-ons external infrared to light up the whole area.

6. Complete Open

With onvif profile-S, you can integrate our smoke detector spy camera to any other 3rd party Onvif NVRs or VMS software.

7. Easy to setup

This camera supports Power over Ethernet (PoE). Single cat5 cable can carry both power and network to this smoke detector spy camera .

Typical Application

Home

Retail

Convenience Store

Workshop

Logistics center

and others

Specification

Power	
Input voltage	+12 VDC
Power consumption	6.0 W (max)
Video	
Sensor type	1/2.8 Type CMOS Sensor
Sensor pixels	1920x1080
Sensitivity	0.5 lx (IR off) 0 lx (IR on)
Main-stream Resolution	1920x1080@25fps; 1280x720@25fps
Sub-stream Resolution	4CIF@25fps; CIF@25fps
Video compression	H.265/H.264 MP (Main Profile)
DWDR	ON/OFF
3D DNR	Yes
Night vision ¹	
IR cut filter	Yes
Lens	
Lens type	3.7 mm pinhole lens
Field of View	H: 76°
Lens mount	Board mounted
Day & Night	Auto ICR Switch
Audio (NOT included)	
Audio input	RCA jack connector
Audio output	RCA jack connector
Audio communication	Two-way, full duplex
Audio compression	G.711 (live and recording)
Local Storage	
Memory card slot	Supports up to 128 GB micro SD card (An SD card of Class 10 or higher is recommended for HD recording)
Recording	Continuous recording, Motion/schedule recording, Alarm Trigger
Onvif Protocol	
Profile-S	Yes

1. The camera can see the external infra-red, require external infrared illuminator to boost up the night vision.

Software Control	
Unit configuration	Via web browser or PC surveillance software
Network	
Protocols	HTTP, TCP/IP, ARP, RTSP, RTP, UDP, SMTP, FTP, DHCP, DNS, DDNS, PPPOE, UPNP, NTP, 802.1x
Ethernet	10/100 Base-T, auto-sensing, half/full duplex, RJ45
Wireless	IEEE 802.11b/g/n
PoE	N/A
Mechanical	
Dimensions	130*50mm
Weight	TBA
Environmental	
Operating temperature Camera	-20 °C to +55 °C (-4 °F to +131 °F)
Storage temperature	-20 °C to +70 °C (-4 °F to +158 °F)
Humidity	10% to 80% relative humidity (non condensing)
Ordering Information	
Smoke Detector Spy Camera	2651-57