

2651-68

Smoke Alarm Camera



Key Vaule Highlight

1. Smart Person Detection

This Smoke Alarm Camera can detect human being accurately in the live video with a smarter algorithm and send push message to your mobile phone.

2. Covert Camera

Install the Smoke Alarm Camera on ceiling give you great advance to monitor the sense without being detected.

3. All-in-One

This camera is a completed hidden security system in a single device. Insert Marco SD card, the Smoke Alarm Camera will start person detected recording.

4. Free app for mobile accessing

You can easily watch the live video, check the recording footage from Smoke Alarm Camera on your mobile phone, tablet or PC.

5. Complete Open

With onvif profile-S, you can integrate the Smoke Alarm Camera to any other 3rd party Onvif NVRs or VMS software.

6. Easy to setup

This camera supports both WiFi and cat5e wire connection which provides great flexibility in installation.

Typical Application

Home

Retail

Convenience Store

Workshop

Logistics center

and others

Specification

| Power | |
|---------------------------|---|
| Input voltage | +12 VDC |
| Power consumption | 6.0 W (max) |
| Video | |
| Sensor type | 1/2.8 Type CMOS Sensor |
| Sensor pixels | 1920x1080 |
| Sensitivity | 0.5 lx (IR off) 0 lx (IR on) |
| Main-stream Resolution | 1920x1080@25fps; 1280x720@25fps |
| Sub-stream Resolution | 4CIF@25fps; CIF@25fps |
| Video compression | H.265/H.264 MP (Main Profile) |
| DWDR | ON/OFF |
| 3D DNR | Yes |
| Night vision ¹ | |
| IR cut filter | N/A |
| Lens | |
| Lens type | 3.7 mm pinhole lens |
| Field of View | H: 76° |
| Lens mount | Board mounted |
| Day & Night | Auto ICR Switch |
| Audio | |
| Audio input | Built-in mic |
| Audio compression | G.711 (live and recording) |
| Local Storage | |
| Memory card slot | Supports up to 128 GB micro SD card (An SD card of Class 10 or higher is recommended for HD recording) |
| Recording | Continuous recording, Motion/schedule recording, Alarm Trigger |
| Onvif Protocol | |
| Profile-S | Yes |

| Software Control | |
|------------------------------|---|
| Unit configuration | Via web browser or PC surveillance software |
| Network | |
| Protocols | HTTP, TCP/IP, ARP, RTSP, RTP, UDP, SMTP, FTP, DHCP, DNS, DDNS, PPPOE, UPNP, NTP, 802.1x |
| Ethernet | 10/100 Base-T, auto-sensing, half/full duplex, RJ45 |
| Wireless | IEEE 802.11b/g/n |
| Mechanical | |
| Dimensions | 130*50mm |
| Weight | TBA |
| Environmental | |
| Operating temperature Camera | -20 °C to +55 °C (-4 °F to +131 °F) |
| Storage temperature | -20 °C to +70 °C (-4 °F to +158 °F) |
| Humidity | 10% to 80% relative humidity (non condensing) |
| Ordering Information | |
| Smoke Alarm Camera | 2651-68 |